





# Model: RN - 40

Rigid Narrow Neck

Overall Length	Overall Width	Gooseneck Length	Deck Length	Deck Height	Rear Length	Rear Height	Ground Clearance
41' 9"	8' 6"	8' 11"	28' 6"	41"	N/A	N/A	N/A



Standard Trailer Dimensions



Weight Capacity 80,000 lbs.

GVWR

Gooseneck	
King Pin Style	Fixed
King Pin Setting	15"
Swing Clearance	87"
5 <sup>th</sup> Wheel Height	48"
King Pin	2"
Ride Height Adj.	N/A

Axle, Suspension, & Running Gear	
# of Axles	2 Spring Suspension Axles
Axle Spacing	49"
Axle Capacity	25,000 lbs.
Brakes	16 1/2" x 7" – 25,000 lbs.
ABS	2S / 1M

Main Deck	
Main Beam	W16x57 Beams A992 Grade 50
Centers	40" Standard
Side Beams	C10x15.3
Crossmembers	W8x10 A992 Grade 50
Spacing	24" Standard
Outriggers	N/A
# of D-Rings	4 per Side
Front Ramps	N/A
Concentrated Load	80,000 lbs. (Within a 16' Span)

Decking / Flooring	
Main Decking	2" Oak Lumber

Wheel Assembly	
Tires	255 / 70R 22.5
Rims	8.25 x 22.5 Steel Wheels

Tail Section	
Beavertail	36"

Finish	
Anticorrosive Undercoat – 2 Coats Epoxy Primer	
2 Coats Gloss Acrylic Enamel Top Coat	
Mud Flaps & Reflective Tape	

Electrical	
Lights	Sealed Modular Wire Harness
Connector	7 Way Connector

Popular Options	
36" x 84" Electric Over Hydraulic Ramps	
Additional Deck Length	
Additional D-Rings	
Air Ride Suspension w/ Lift Axle	
ISO Twist Locks	
Lockable Storage	
Manual Height Control	
Neck Fenders	
Rolling Tailboard	
Winch Kit	

Ramps	
24" x 60" Manual Ramps	

For additional information on your Witzco Challenger Trailer contact the dealer nearest you.

Call: (941) 922 – 5301 \* Toll Free: 1-888-922-9900 \* info@witzco.com